



Allied Lighting

jc639 U.S. PTO
02/17/99

A

Division of Allied Universal Suppliers, Inc.

16776 Bernardo Center Drive, Ste. 110B
San Diego, CA 92128-2558

February 17, 1999

Commissioner of Patents and Trademarks
Washington, D.C. 20231

jc542 U.S. PTO
09/25/306
02/17/99

Enclosed is a patent application for our lighting fixture. It includes 3 pages of drawings, 15 pages of patent application and a check for \$487 for the patent fee. The application was prepared by our patent attorney and I'm filing it as an individual. The joint inventor refused to sign a declaration stating that there are (2) two inventors. The other inventor is William A. Hein, 670 6th Street, Manhatten Beach, CA 90266, (310) 374-7763.

I am enclosing a self addressed stamped post card that I ask you sign and return stating that our application has been received.

If I can assist you in any way please call me at (800) 480-8013. Thank you in advance for your help.

Best Regards,

ALLIED LIGHTING

Peter C. Sara
President, Principal

enclosures

1
LIGHT FIXTURE

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation in part patent application of U.S. Application Serial No. 29/094,329, titled "Light Fixture", filed 09/30/98 now U.S. Patent No. .

FIELD OF THE INVENTION

The present invention relates generally to light fixtures and, more particularly, to light fixtures suitable for illuminating flat surfaces.

BACKGROUND OF THE INVENTION

Surface illuminating devices are well known. For example, light fixtures are used in museums to illustrate paintings and on highways to light up directional signs. In another common use, conventional light fixtures are utilized to illuminate outdoor advertising, found along highways and thoroughfares.

The well-known term "billboard" is often used for poster panels and bulletins. A typical bulletin is utilized to advertise printed or hand painted messages and is usually found in high density traffic locations. The bulletin typically has an area of 672 square feet, having a height of about 14 feet and a width of about 48 feet. Poster panels are smaller, with an area of about 300 square feet, a height of about 12 feet and a width of about 25 feet. A poster panel is typically about 6 feet high and approximately 12 feet wide, having an area of about 72 square feet. While this specification sets forth the present invention as it relates to bulletins, it will be recognized that the present invention has application to a variety of cases wherein it is desirable to illuminate a large flat surface. For convenience, the "billboard" will be used herein in reference to such surfaces.

In a many cases, billboards display graphic advertisements or public service messages and the boards are oriented so as to be seen by motorists and pedestrians passing them during travel. Typically, a billboard having a length of 48 feet is illuminated from below by four light fixtures equidistantly spaced

5 along a bottom surface of the board and separated from the board by about 4
to six feet. An important desirable characteristic of billboard light fixtures is
that, when spaced along the lower edge of a billboard, they provide uniform
lighting to the board so that no dark spots or shadows occur across the surface
thereof. This characteristic is generally not found in conventional billboard
10 light fixtures.

It is not uncommon in a billboard lighting system, utilizing four light
fixtures, for the billboard to have four islands of bright illumination with
shadowed areas at the periphery of the islands and between the islands of
light. The result is an illuminated billboard that is not esthetically attractive
and which, in some respects, fails to convey the advertiser's message because
15 of uneven illumination or shadows on the board.

Thus, there is a need for a light fixture, adapted for use in illuminating
flat surfaces such as billboards, that can illuminate the surface in a generally
uniform manner while substantially reducing shadowed areas.

20 In view of the environment in which the device is utilized, such a light
fixture should have some weather resistant capabilities since it will be exposed
to a variety of changing and, sometimes severe, weather conditions. It should
be resistant to invasion by insects and other pests and it should be easily
maintained and capable of being opened quickly and easily for bulb
25 replacement and maintenance. In addition, the light fixture should have good
aerodynamic characteristics so as to withstand high winds without damage.

Further, the fixture should not contribute to "light pollution" by
scattering light away from the object being illuminated. Still further, the light
fixture should have a low profile so that it would not draw the eye of the
30 observer to itself but, instead, would induce the observer to look at the surface
being illuminated.

In some cases, conventional light fixtures fail to satisfy the aforesaid
criteria.

5 In view of the foregoing, there is a need for a light fixture having a low profile, readily accessible for repair and bulb replacement and aerodynamically shaped to help reduce wind damage. Desirably, such a light fixture could provide a broad spectrum of illumination over a flat surface so that, when used in combination with similar fixtures, a large billboard surface could be
10 illuminated in a relatively uniform manner while substantially reducing light pollution.

Ideally, such a light fixture would be low in cost to manufacture, being constructed of readily available materials.

SUMMARY OF THE INVENTION

15 In accordance with the present invention, there is provided a light fixture having a base for housing a light producing source and a flat plate disposed within the base. The plate has a well formed in it, the well having light reflecting walls. A lamp socket is located in a light reflecting bottom wall of the well. A plurality of light reflecting elements is attached to the plate and a pair
20 of light reflecting assemblies, one on either side of the well, is fixed to the plate. Each light reflecting assembly includes a plurality of light reflecting fins affixed to the plate and projecting at an angle away from the plate. A frame having a convex lens affixed thereto is hingedly attached to the base. A light shield is fixed to the frame for reducing dispersion of unwanted light.

25 The present invention affords several advantages. For example, the light reflecting elements, walls and fins cooperate to distribute light over a flat surface uniformly, in an efficient and effective manner. When a billboard is illuminated by the present invention, shadows and dark spots are substantially reduced and an aesthetically pleasing result is obtained.

30 The light fixture of the present invention is constructed of readily obtainable materials and it has a rugged construction for use in varying weather conditions. The provision of a light shield helps to reduce unwanted light pollution and, as a result, the fixture is usable in an urban environment.

5 In addition, the light fixture of the present invention is easy to install, mechanically simple, economical and easy to maintain and service.

Other aspects and advantages of the present invention will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, illustrating by way of example the principles of the invention.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a perspective view of the light fixture of the present invention showing the housing and lens assembly in separated relationship;

FIG. 2 is a top plan view of the light fixture;

FIG. 3 is a sectional view taken along the line 3 - 3 of FIG. 2;

FIG. 4 is a perspective view of the base of the light fixture showing some of the components thereof; and,

FIG. 5 is a schematic depiction of the right one half of a billboard showing photometric readings taken at various places on a billboard illuminated by four light fixtures of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings, and more particularly to FIGS. 1 - 4 thereof, there is shown the light fixture 10 of the present invention. The fixture 10 includes a generally rectangular base 11, having a cover 15 connected by a hinge 17. The base 11 described and depicted herein is generally rectangular in plan view and, for convenience, it may be regarded as having front, back, left and right sides. It will be recognized that light fixtures having bases with other shapes, round or oval for example, are within the contemplation and scope of the present invention.

The cover 15 is fixed to the base 11 by means of latches 19, which engage hooks 21 on the cover 15. The cover 15 includes a frame 23 that surrounds and holds a conventional convex lens 25. A light shield 27, affixed to the frame 23, helps to prevent unwanted light scattering. The shield extends across a rear portion of the frame 23, and wraps partially along the sides of the

5 frame 23. The light shield 27 has a height approximately equal to the height of the lens 25.

10 The base 11 includes a right sidewall 33, a left sidewall 34, a front wall 25 and a rear wall 37. In the presently preferred embodiment, the walls are constructed of stamped aluminum. A knuckle assembly 41 extends from a bottom wall 38 and includes a joint 43 and a pipe 45. The assembly 41 permits water tight and weatherproof access to the interior of the fixture 10 for provision of electrical lines. The joint 43 enables adjustment of the angle at which the light fixture 10 is oriented toward a billboard to be illuminated.

15 The base 11 includes a silicon gasket 29 which serves to provide a weather tight seal when the cover 15 is closed and clamped against the base 11. A switch 46, located near the front of the light fixture 10, within the gasket 29, permits power to the fixture 10 to be turned off and on during routine maintenance and lamp replacement.

20 The base 11 includes a generally rectangular flat sheet aluminum plate 51. Brackets, such as the brackets 31, support the plate 51 which is fixed thereto in a conventional manner. A well 75 is formed in the plate 51. Defining the well 75 are a light reflecting front wall 76, a light reflecting rear wall 81, light reflecting left and right sidewalls 79 and 77, respectively, and a bottom wall 82. An opening 82a is formed in the bottom wall 82 for receipt of a lamp socket 53 that, in turn receives a lamp L. Each one of the light reflecting walls defining the well 25 is of sheet aluminum construction. The walls 76, 77 and 79 are each generally trapezoidal in shape each having a foot portion 76a, 77a and 79a respectively, bent at about a right angle to the wall surface. The foot portions 76a, 77a and 79a are fixed to the plate 51, in a conventional manner, by fastening means such as rivets 68. It will be noted that the rear wall 81 extends above the surface of the plate 51 and describes an angle B with the plate 51 of about 45°. The rear wall 81 is of sheet aluminum construction and generally trapezoidal in shape. The top edge of the wall 81 is truncated,

25

30

5 having portions on the left and right sides removed. The light reflecting surfaces of the light reflecting walls 76, 77, 79, 81 and 82 each have a polished mirror-like finish.

10 A light reflecting element 71, of sheet aluminum construction, is disposed forward of the well 75. The element 71 includes a short light reflecting vertical wall 71b that is fixed at a flange 71a by rivets 68 to the plate 51. With respect to the plate 51, the light reflecting element 71 slopes downwardly, toward the well 75, at an angle A of approximately 45°, to a flange 71c which is affixed by rivets 68 to the upper surface of the plate 51.

15 In a similar manner, at the rearward portion of the base 11, there is a light reflecting plate 73 that is also of sheet aluminum construction. The reflecting plate is fixed to the plate 51, at a flange 73b, by rivets 68. With respect to the plate 51, the reflecting plate 73 slopes away from the well 75 at an angle D of about 45°. The light reflecting surfaces of the light reflecting element 71 and the light reflecting plate 73 each have a polished mirror-like finish.

20 As mentioned, while the base 11 is generally rectangular in shape, other shaped bases are within the scope of the present invention. Although the shape of the base might change from one embodiment to another, the light fixture 10 may be regarded as being generally symmetrical about a line M which, as shown in FIGS. 2 and 4, divides, or bisects, the light fixture 10 into symmetrical halves. As the term is used herein, "bisects" means "to divide into two generally equal halves".

25 Lateral light reflecting assemblies 93 and 94 will now be considered, with reference to FIGS. 1-4. The lateral assemblies are disposed laterally of the bisecting line M with the assembly 93 on the right side and the assembly 94 on the left. Each one of the assemblies 93 and 94 includes three trapezoidal light reflecting fins. Each one of these fins is of sheet aluminum construction and each is fixed to the plate 51 by fastening means such as the rivets 68. It will be

5 understood that the light reflecting surfaces of each one of the trapezoidal fins have a polished mirror-like finish.

The light reflecting fins comprising the assembly 93 are the fins 55, 57 and 59. Each fin is affixed by rivets 68 to the plate 51 at flanges 55a, 57a and 59a, respectively. Similarly arrayed on the left side of the base 11 and
10 comprising the assembly 94 are the fins 61, 63 and 65 having respectively flanges 61a, 63a and 65a fixed by rivets 68 to the plate 51.

Each one of the light reflecting fins 55, 57, 59, 61, 63 and 65 is canted slightly laterally away from the vertical with respect to the plate 51. In this regard, the fins 59 and 65 each describe an angle C (FIG.3) of between about 50° and 60° with a preferred angle of about 55°. The fins 57 and 63, with
15 respect to a line perpendicular to the plate 51, each describe an angle E (FIG. 4) of between about 55° and 65° with a preferred angle of about 60°. The fins 55 and 61, with respect to a line perpendicular to the plate 51, each describe an angle F (FIG. 4) of between about 65° and 75° with a preferred
20 angle of about 70°.

Each one of the fins in the lateral assemblies 93 and 94 is trapezoidal in shape and each one of a given assembly differs from the other two fins of the assembly. By way of example, the assembly 93 will now be discussed. It will be understood that the descriptions of the fins 55, 57 and 59 apply equally to
25 their counterparts, the fins 61, 63 and 65, respectively, comprising the assembly 94.

The fin 55 is generally rectangular in shape and constructed of aluminum. It is attached to the reflector plate 51 at a flange 55a by means of rivets 68. The fin 55 and the flange 55a are aligned generally parallel to the
30 right sidewall 33 of the base 11. It will be understood that if the base had a round or oval construction, the fin 55 and the flange 55a would be aligned generally parallel to a line bisecting the elements 71 and 73. The top surface of

5 the fin 55 is not squared but has a small wedged shaped portion removed at the forward portion of the fin.

10 The fin 57 is located between the fin 55 and the fin 59. The fin 57 includes a flange 57a fixed to the plate 51 by rivets 68. The fin 57 is trapezoidal in shape and the fin and the flange 57a are disposed at an angle of about 30° angle to the right sidewall 33 or at a similar angle to a line bisecting the elements 71 and 73. The fin 57 is also of aluminum construction, having a pair of parallel sides and a truncated top. The fin 57 extends laterally with respect to the fin 55, overlapping the fin 55.

15 The fin 59 is fixed, at a flange 59a, to the plate 51 by rivets 68. The fin 59 is disposed so as to describe the hypotenuse of a right triangle formed by the right sidewall 33 and the rear wall 37. Thus, the fin 59 and the flange 59a are disposed at an approximate 45° angle to the right sidewall 33 or at a similar angle to a line bisecting the elements 71 and 73. The fin 59 is also of aluminum construction. It has a generally rectangular shape having a pair of sidewalls 59a and 59b and a top wall 59c. The fin 59 extends laterally with respect to the fin 57, overlapping the fin 57.

20 In a presently preferred embodiment of the present invention, the bottom wall 38 slopes downwardly to help form a space 83, defined by the sidewalls 33 and 34, the bottom wall 38 and the front wall 35. The space 83 enables convenient storage of lamp wiring and ballast (neither shown), without substantially increasing the size of the light fixture 10.

The light fixture 10 is suitable for use with a variety of conventional lamps. In a presently preferred embodiment, the lamp L is a metal halide 400W lamp manufactured by Venture Lighting, Solon, Ohio.

30 In operation, the light fixture 10, by virtue of the plurality of highly polished fins and reflective surfaces, produces a uniform light over a large flat surface. For example, by reference to FIG. 5, there is shown schematically the right one half of a typical billboard B erected on a leg 101 and illuminated by

5 two light fixtures 10. Distances in feet from the bottom edge of the billboard B
are shown along the vertical to the right of the billboard while distances in feet
from the right edge of the billboard are shown in a horizontal display above the
board. Typically, the billboard B has a height of about 14 feet and a width of
about 48 feet. In tests performed on a billboard having such dimensions, four
10 light fixtures 10 were disposed equidistantly along the lower edge of the
billboard. Photometric values were measured at various places on the billboard
B. The values obtained, in foot-candles, are shown in FIG. 5. Identical,
symmetrical values were obtained on the left side (not shown) of the billboard
B. It will be seen that light fell on all portions of the billboard B with general
15 uniformity. The result obtained shows that dark spots and areas of darkness
between light segments have been substantially eliminated.

The present invention may be embodied in other specific forms without
departing from its spirit or essential characteristics. The described
embodiments are to be considered in all respects only as illustrative and not
20 restrictive. The scope of the invention is, therefore, determined by the appended
claims rather than by the foregoing description. All changes, which come
within the meaning and range of equivalency of the claims, are to be embraced
within their scope.

5 What is claimed is:

1. A light fixture for illuminating a surface, comprising:

a base for housing a light producing source;
a lens covering at least a portion of said base;
a plate disposed within said base; and

10 a plurality of light reflecting fins affixed to said plate and projecting from
said plate in a direction away from said plate.

2. The light fixture according to claim 1, wherein said lens is convex.

3. The light fixture according to claim 2, wherein said fixture includes a
frame moveably connected to said base, said lens being fixed to said frame.

15 4. The light fixture according to claim 3, wherein said frame includes light
shielding means for reducing unwanted dispersion of light.

5. The light fixture according to claim 1, wherein said plate includes means
formed therein for defining a well, said well defining means including a
plurality of light reflecting sidewalls and a light reflecting bottom wall.

20 6. The light fixture according to claim 5, wherein said well defining means
includes a plurality of light reflecting walls, each one of said light reflecting
walls having a trapezoidal configuration.

7. The light fixture according to claim 5, wherein said well defining means
includes a light reflecting front wall.

25 8. The light fixture according to claim 5, wherein said well defining means
includes a light reflecting rear wall.

9. The light fixture according to claim 6, wherein each one of said plurality
of light reflecting sidewalls includes a flange and means for fastening said
flange to said plate.

30 10. The light fixture according to claim 5, wherein said fixture includes a
front wall and a light reflecting element disposed on said plate between said
well and said front wall.

- 5 11. The light fixture according to claim 10, wherein said light reflecting element includes a light reflecting surface, said surface being inclined, with reference to said plate, at an angle of between 30° and 50°.
12. The light fixture according to claim 10, wherein said light reflecting element includes a light reflecting surface, said surface being inclined, with
10 reference to said plate, at an angle of about 45°.
13. The light fixture according to claim 5, wherein said fixture includes a rear wall and a light reflecting element disposed on said plate between said well and said rear wall.
14. The light fixture according to claim 13, wherein said light reflecting
15 element includes a light reflecting surface, said surface being inclined, with reference to said plate, at an angle of between 30° and 50°.
15. The light fixture according to claim 13, wherein said light reflecting element includes a light reflecting surface, said surface being inclined, with reference to said plate, at an angle of about 45°.
- 20 16. The light fixture according to claim 5, including a pair of light reflecting assemblies, each one of said light reflecting assemblies being disposed laterally of a line bisecting said base.
17. The light fixture according to claim 16, wherein each one of said light reflecting assemblies includes a plurality of light reflecting fins.
- 25 18. The light fixture according to claim 17, in which a first one of each of said plurality of light reflecting fins is trapezoidal in configuration.
19. The light fixture according to claim 18, in which said first one of each of said plurality of light reflecting fins is canted laterally away from the perpendicular with reference to said plate at an angle of between 65° and 75°.
- 30 20. The light fixture according to claim 18, wherein said first one of each of said plurality of light reflecting fins is elongated, having a long axis parallel to a plane bisecting said front light reflecting element and said rear light reflecting element.

- 5 21. The light fixture according to claim 18, wherein said first one of each of said plurality of light reflecting fins includes a flange, said flange being affixed to said plate.
22. The light fixture according to claim 17, in which a second one of each of said light reflecting fins is trapezoidal in configuration, having a truncated top.
- 10 23. The light fixture according to claim 22, in which said second one of each of said plurality of light reflecting fins is canted laterally from the perpendicular with reference to said plate at an angle of between 55° and 65° .
24. The light fixture according to claim 22, wherein said second one of each of said plurality of light reflecting fins is elongated, having a long axis forming an angle of about 30° to a plane bisecting said front light reflecting element and said rear light reflecting element.
- 15 25. The light fixture according to claim 22, wherein said second one of each of said plurality of light reflecting fins includes an edge, said edge extending laterally to said first one of each of said plurality of light reflecting fins.
- 20 27. The light fixture according to claim 22, wherein said second one of each of said plurality of light reflecting fins includes a flange, said flange being fixedly attached to said plate.
28. The light fixture according to claim 17, wherein said plurality of light reflecting fins includes a third fin.
- 25 29. The light fixture according to claim 28, wherein said third one of said plurality of light reflecting fins fin is generally rectangular in shape.
30. The light fixture according to claim 28, wherein said third one of said plurality of light reflecting fins is disposed at a 45° angle to a plane bisecting said front light reflecting element and said rear light reflecting element.
- 30 31. The light fixture according to claim 27 wherein said third one of said plurality of light reflecting fins includes a flange, said flange being fixed to said plate.

- 5 32. The light fixture according to claim 27 wherein said third one of said plurality of light reflecting fins includes an edge, said edge extending laterally to said second one of said plurality of light reflecting fins.
33. The light fixture according to claim 1, wherein said fixture further includes an elongated light reflecting plate, said plate having edges, said edges
10 extending laterally beyond each one of said third one of said plurality of light reflecting fins of said plurality of light reflecting assemblies.
34. The light fixture according to claim 33, wherein said light reflecting plate includes a flange, said flange being fixed to said plate.
35. The light fixture according to claim 33, wherein said light reflecting plate
15 includes a first surface disposed at approximately 45° to the surface of said plate, being canted away therefrom.
36. The light fixture according to claim 18, including a front reflective element.
37. The light fixture according to claim 36, wherein said front reflective
20 element includes a reflective surface disposed at about a 45° angle to said plate, said surface angling outwardly away from a line bisecting said base, said front reflective element further including a perpendicular wall.
38. The light fixture according to claim 37, wherein said perpendicular wall includes a flange, said flange being fixed to said plate.
- 25 39. The light fixture according to claim 1, wherein said fixture further includes switch means for interrupting and restoring electrical power to said light source.
40. The light fixture according to claim 1, including cover securing means.
41. The light fixture according to claim 1, including wire routing means for
30 routing wire into said base.
42. The light fixture according to claim 1, including a pair of sidewalls, a front wall, a rear wall and a bottom wall wherein said bottom wall is configured for receipt therewithin of light ballast means.

43. 43. The light fixture according to claim 42, wherein said pair of sidewalls, said front wall and said bottom wall define a space within said base, said space being suitable for disposition therewithin of lamp ballast.

10

15

20

25

30

ABSTRACT OF THE DISCLOSURE

5

10

15

A light fixture having a base for housing a light producing source and a flat plate disposed within the base. The plate has a well formed in it, the well having light reflecting walls. A lamp socket is located in a light reflecting bottom wall of the well. A plurality of light reflecting elements is attached to the plate and a pair of light reflecting assemblies, one on either side of the well, is fixed to the plate. Each light reflecting assembly includes a plurality of light reflecting fins affixed to the plate and projecting at an angle away from the plate. A frame having a convex lens affixed thereto is hingedly attached to the base. A light shield is fixed to the frame for reducing dispersion of unwanted light.

FIG. 1





FIG. 3






FIG. 2




FIG. 5




FIG. 4